

P.S. METALLIC

Description Plotter cut heat seal material with adhesive polyester backing and a metallic finish. Due to the unique nature of its metallic surface, it is not suggested for very small details and multilayer applications. Avoid bending the application once transferred. Average thickness: **200 micron**

Basic information Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:
Plotter settings (eg. with SUMMACUT D60R plotter)
Blade: **new for high thicknesses**
Minimum required pressure: **70 gf**
Transfer setup
Temperature: **160°C**
Time: **15"**
Pressure: **medium (3÷4 bar)**

Application instructions Mirror cut the material
Weed the exceeding material
Place the material on the garment with its polyester backing
Heat apply
Wait 3÷5", then remove the support

Suitable textiles Cotton, polyester and blends of these materials
(not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
Cold – hand wash recommended – inside out
Do not use bleach or other aggressive chemical agents
Dry clean: **no**
Tumble dry: **no**



Siser s.r.l.

Viale della Tecnica n° 18
36100 Vicenza - Italy
Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.it

N.B.

All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.